



## 4T SG 10w40

### Typical Specifications

Engine Armour 4T SG 10w40 Motorcycle Oil is designed to provide wear protection, sludge and varnish protection, and thermal stability for superior performance in four-cycle motorcycle applications. Blended with high-quality base stocks and performance chemistry, the Engine Armour 4T is formulated for superior operation in high-revving, high-temperature motorcycle engines.

Engine Armour 4T SG 10w40 Motorcycle Oil is blended to give superior performance in those engines and transmissions that have common sump and require specialized frictional characteristics for clutches and wet brakes.

Applications: (API – SG), (JASO 4T: MA)

<b>API Gravity</b>	<b>28.0</b>
<b>Viscosity cSt</b>	
<b>@ 40 C</b>	<b>92</b>
<b>@ 100 C</b>	<b>13.5</b>
<b>Viscosity Index</b>	<b>147</b>
<b>Flash Point C</b>	<b>200</b>
<b>Pour Point C</b>	<b>-36</b>
<b>% Weight Ash</b>	<b>0.6</b>
<b>Visual Color</b>	<b>N/A</b>

\*Engine Armour 4T SG meets or exceeds API SG and JASO MA.

The data presented in this specification sheet are believed to be accurate; however, Engine Armour shall not be liable for its content and makes no warranty with respect thereto.