



Chrysler ATF+3 Type 7176E Fluid

Typical Specifications

Engine Armour Chrysler ATF+3 Type 7176 E Fluid is recommended for Chrysler and Daimler Chrysler transmissions recommending ATF+3 or ATF+2,, and covered by specification MS 7176E/D. This Fluid is also recommended where Allison C-3 and C-4 fluids are required. This chemistry offers excellent low temperature properties and improved anti-shudder properties.

Applications: (Dexron®, Dexron® II, III, III H), (Mercon®), (Chrysler: 7176E (ATF+3), 7176D (ATF+2)), (Allison: C-4), (Caterpillar: TO-2), (GM: Type A), (Ford: M2C33-A/B, M2C138-CJ, M2C116-H), (API: GL-1), (Eaton: Fuller Division), (Denison: HF-0/1/2), (Power Steering Units**)

API Gravity	31.5
Viscosity cSt	
@ 40 C	34.5
@ 100 C	7.50
Brookfield Vis	<20,000
Viscosity Index	180
Flash Point C	190
Pour Point C	-40

**Transmission Fluid also applicable in power steering units; check owners' manual.

The data presented in this specification sheet are believed to be accurate; however, Engine Armour shall not be liable for its content and makes no warranty with respect thereto.