



## DX III H/M (ATF)

### Typical Specifications

Engine Armour DX III H/M Automatic Transmission Fluid (ATF) is a premium multipurpose Automatic Transmission Fluid approved for Dexron® III H specification and recommended for many transmission systems used throughout the world, requiring Dexron®III H/Mercon ATF as well as Allison C-3 and C-4 fluids. Engine Armour DX III H/M is recommended for use in all transmission, hydraulic systems, and power steering units manufactured by American, European, Korean, Japanese and other manufactures from around the world specifying Dexron®III H/Mercon® type transmission fluid.

Applications: (Dexron®, Dexron® II, III, III H), (Mercon®), (Chrysler: 7176D ATF+2), (Allison: C-4), (Caterpillar: TO-2), (GM: Type A), (Ford: M2C33-A/B, M2C138-CJ, M2CI16-H), API: GL-1), (Eaton: Fuller Division), (Denison: HF-0/1/2), (Power Steering Units\*\*)

<b>API Gravity</b>	<b>32.5</b>
<b>Viscosity cSt</b>	
<b>@ 40 C</b>	<b>34.6</b>
<b>@ 100 C</b>	<b>7.10</b>
<b>Brookfield Vis</b>	<b>&lt;20,000</b>
<b>Viscosity Index</b>	<b>170</b>
<b>Flash Point C</b>	<b>190</b>
<b>Pour Point C</b>	<b>-49</b>

\*\*Transmission Fluid also applicable in power steering units; check owners' manual.

The data presented in this specification sheet are believed to be accurate; however, Engine Armour shall not be liable for its content and makes no warranty with respect thereto.