



GL-5 Gear Oils

Typical Specifications

Engine Armour Multipurpose High Performance GL-5 Gear Oils are high performance gear oils that meet the latest specifications for today's high performance automobiles, trucks and industrial applications. These oils are manufactured to meet extreme pressure (EP) applications and are designed to resist oxidation and allow for longer oil change intervals.

These gear oils are recommended for use in differentials, including most limited slip differentials, transmissions, transfer cases, planetary and industrial gear boxes where extreme pressure lubricants are required. These oils meet or exceed the recommendations for API GL-5 and API MT-1; MIL-L-2105E (MILPRF 2105E), and Mack GL-J Plus.

Applications: (API: GL-1, GL-2/3, GL-4, GL-5, MT-1), (MIL-PRF-2105E), (Mack: GO-J), (Outboards 7 Stem Drives)

GL-5	75w90	80w90	85w140
API Gravity	27.6	27.6	25.5
Viscosity cSt			
@ 40 C	120	142	352.0
@ 100 C	14.0	14.2	26.20
Brookfield Vis	<150,000	<150,000	<150,000
Viscosity Index	116	97	98
Flash Point C	200	230	250
Pour Point C	-45	-30	-24

The data presented in this specification sheet are believed to be accurate; however, Engine Armour shall not be liable for its content and makes no warranty with respect thereto.