



## Premium Motor Oils

### Typical Specifications

Engine Armour Premium Motor Oils are quality line of straight mineral crankcase engine oils and general purpose oils for gasoline and diesel engine applications that operate in less than severe conditions.

Engine Armour Premium Motor Oils are available in mono-grade and multi-viscosity configurations; the multi-viscosity products contain shear stable viscosity index improvers, assuring easier starts in cold temperatures and less thinning at higher temperatures. These oils are manufactured to meet the requirements of the American Petroleum Institute (API) service "SA/SB". **NOT** recommended for engines demanding API SM, SL, SJ, SH performance, or any ILSAC level such as GF-1, GF-2, GF-3 and/or GF-4.

Applications: (API: SB, SA)

<b>SAE Grade</b>	<b>30</b>	<b>40</b>	<b>50</b>	<b>10w30</b>	<b>10w40</b>	<b>15w40</b>	<b>20w50</b>
<b>API Gravity</b>	<b>23.2</b>	<b>21.8</b>	<b>20.6</b>	<b>28.6</b>	<b>29.6</b>	<b>29.6</b>	<b>29.4</b>
<b>Viscosity cSt</b>							
<b>@ 100 C</b>	<b>10.10</b>	<b>13.50</b>	<b>17.50</b>	<b>9.90</b>	<b>12.90</b>	<b>13.20</b>	<b>16.90</b>
<b>Flash Point C</b>	<b>200</b>	<b>210</b>	<b>220</b>	<b>210</b>	<b>220</b>	<b>220</b>	<b>220</b>
<b>Pour Point C</b>	<b>-12</b>	<b>-10</b>	<b>-08</b>	<b>-35</b>	<b>-32</b>	<b>-27</b>	<b>-18</b>

The data presented in this specification sheet are believed to be accurate; however, Engine Armour shall not be liable for its content and makes no warranty with respect thereto.