



Supreme Motor Oils

Typical Specifications

Engine Armour Supreme Motor Oils are high quality detergent/dispersant motor oils recommended for gasoline and diesel engines manufactured by American, European, Japanese, Korean and other engine manufactures from around the world. These oils are manufactured to meet the requirements of API SG, SF/CF, CF-2 and CF-4 as well as (ACEA) A3/B4, A3/B3, and A1/B1.

Engine Armour Supreme Motor Oils are manufactured from select blends of high quality base oils and additives to promote long engine life, protect against rust, corrosion and harmful oxidation, and are designed to help reduce engine wear and oil consumption. The multi-grade Motor Oils are coupled with a premium viscosity modifier to assure easy starts in cold temperatures and protect against oil thinning at higher temperatures. Also these energy conserving formulations may result in fuel savings to the consumer.

Applications: (API: SG, SF, SB, SA, CF/CF-2, CF-4), (ACEA: A3/B4)

SAE Grade	10	30	40	50	5w30	10w30	10w40	15w40	20w50
API Gravity	31.2	29.4	28.0	27.5	30.5	29.5	30.0	29.0	28.9
Viscosity, cSt									
@100 C	5.0	11.0	14.60	17.90	10.20	10.50	13.50	14.00	18.00
@ 40 C	29.0	100.0	141.0	189.0	60.0	69.0	97.0	100.0	165.0
Vis. Index	100	100	100	100	157	140	145	135	125
Flash Point C	220	220	220	230	190	200	200	210	220
Pour Point C	-12	-12	-09	-09	-39	-35	-32	-27	-18

The data presented in this specification sheet are believed to be accurate; however, Engine Armour shall not be liable for its content and makes no warranty with respect thereto.