



## TO-4 Fluids

### Typical Specifications

Engine Armour TO-4 Fluids meet or exceed Caterpillar's newest heavy duty TO-4 transmission requirements, providing greater extended transmission durability over the previous TO-2 fluid. In the market place this fluid is referred to as a "TDTO" fluid. The Engine Armour TO-4 Fluids may also be used as a diesel crankcase oil meeting the API CF and CF-2 performance classifications and wherever Allison C-4 fluid is recommended.

Applications: (API: GL-1), (Denison HF-1), (Power Steering Units\*\*)

<b>TO-4</b>	<b>10</b>	<b>30</b>	<b>50</b>
<b>API Gravity</b>	<b>26.5</b>	<b>28.7</b>	<b>26.7</b>
<b>Viscosity cSt</b>			
<b>@ 40 C</b>	<b>40.7</b>	<b>95.0</b>	<b>209.0</b>
<b>@ 100 C</b>	<b>6.3</b>	<b>10.9</b>	<b>17.70</b>
<b>Viscosity Index</b>	<b>100</b>	<b>100</b>	<b>100</b>
<b>Flash Point C</b>	<b>200</b>	<b>220</b>	<b>240</b>
<b>Pour Point C</b>	<b>-27</b>	<b>-18</b>	<b>-9</b>

\*\*Transmission Fluid also applicable in power steering units; check owners' manual.

The data presented in this specification sheet are believed to be accurate; however, Engine Armour shall not be liable for its content and makes no warranty with respect thereto.