



# Tractor Hydraulic Booster & Stop Leak

## Typical Specifications

Engine Tractor Hydraulic Booster & Stop Leak is a solvent free product designed to extend the life of your equipment while reducing down time and major overhauls. This product will boost oil pressure, reduce seal leaks and reduce heat while increasing the life of your fluid.

Engine Tractor Hydraulic Booster & Stop Leak is designed for use in all kinds of farm equipment, off-highway machinery, industrial tractors, final drives, power take-off units, wet brakes, power steering units and hydraulic systems.

New state of the art chemistry combined with high quality base stocks and extremely shear-stable viscosity modifiers offer a performance level that agriculture and industrial users have not seen before. This fluid is suitable for use in all major OEM equipments.

### Typical Inspection Data:

<b>API Gravity</b>	<b>23.0</b>
<b>Specific Gravity:</b>	<b>0.91586</b>
<b>Lb/gal:</b>	<b>7.627</b>
<b>Viscosity Index</b>	<b>93</b>
<b>Viscosity cSt</b>	
<b>@ 40 C</b>	<b>750</b>
<b>@ 100 C</b>	<b>43.0</b>
<b>Flash Point C</b>	<b>210</b>
<b>Color</b>	<b>&lt;2.5</b>

### Recommended Usage:

10% - 20% - Prevent and stop seal leaks.

30% - 40% - Restore full hydraulic pressure in worn systems.

The data presented in this specification sheet are believed to be accurate; however, Engine Armour shall not be liable for its content and makes no warranty with respect thereto.